



Size : 1 L

COVERAGE
1 L = ± 40sq.m

DRYING TIME
24h before painting

Easy
to
APPLY

INCREASES

**FLOORING
POROSITY**

This product is designed for a correct preparation of any **tiled, marble or concrete flooring before renovation. It improves paint adhesion.**

EASY, FAST and EFFICIENT !

- INCREASES flooring porosity.
- IMPROVES paint adhesion.
- De-polishes smooth surfaces such as tiles.
- Deeply cleans floors and sealants.
- IMPROVES porosity and REMOVES milt concrete.
- Easy application with a brush broom.
- Concentrate to dilute.



PREPARATION FOR FLOORING

FOR A SUCCESSFUL PROJECT

This product is designed for untreated or painted tiled, marble or concrete flooring that has not been waxed or oiled.

Not suitable for wooden, wood derivative or laminate flooring.

On new cement or concrete: wait until the surface has completely dried out i.e. a minimum of 3 months.

> STEP 1 - PREPARATION

• Wash

the floor with a soda-based (alkaline) cleaner to remove as much grease as possible..

• Dilution

The concentration of V33 FLOOR PREPARATION PRODUCT will depend on the porosity or soiling of the floor

- > Not heavily soiled or old cement: 1L + 30L water = 40 sqm
- > Moderately soiled, smooth, non-porous: 1L + 10L water = 12 sqm

The concentration can be increased if necessary.

This product is not a substitute for washing the surface prior to painting.

> STEP 2 - APPLICATION

TOOLS : Watering can and stiff broom

Wear protective gloves and glasses. Shake the can before use.

1. Pour the appropriate amount of V33 FLOOR PREPARATION PRODUCT into the water and then mix, taking care not to splash it. Wear protective gloves and glasses.
2. Use a watering can to ensure uniform distribution of the preparation over the entire surface..
3. Vigorously scrub the floor with a stiff broom, paying special attention to the grouting, and then leave for 30 mins.
4. Rinse thoroughly with clean water. Repeat until all grease, laitance or cement dust has been fully removed. Leave to dry for at least 24 hours.
5. Then apply V33 TILED FLOORING Renovation paint to the tiling or marble.



DANGER

Contains alcohol, C9-C11-iso, C10-rich, ethoxylate. H314: Causes severe skin burns and eye damage. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301 + P330 + P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take o. immediately all contaminated clothing. Rinse skin with water/shower. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501: Dispose of contents/container to a waste collection center (contact the local authority). Contains 15% or over but less than 30%: Phosphoric acid, 5% or over but less than 15%: Non-ionic surfactants. DO NOT ALLOW TO FREEZE.