



ASPECT  
Satin

COVERAGE  
750 ml = ± 10 sq.m per coat

DRYING TIME  
BETWEEN COATS  
24 H

COMPLETE DRYING  
TIME  
72 H



ΑΠΕΥΘΕΙΑΣ ΕΦΑΡΜΟΓΗ ΣΤΗΝ ΕΠΙΦΑΝΕΙΑ  
DIRECT APPLICATION

Size : 750 ml

This paint is designed for **ceramic tiles, wall tiles, border tiles, glass bricks....**

## EASY, FAST and EFFICIENT !

- 2 in 1 NO UNDERCOAT.
- PERFECT TENSE.
- Resistant to repeated contact with water.
- Resistant to care and maintenance products: shampoos, shower gels, traditional household products, anti-limestone products, diluted bleach, white vinegar...
- Does not flake - the paint film is highly durable to temperature variations, such as hot and cold water.
- Washable.
- Water-based paint.

COLOURCHART

White

Feather

Carbonate  
Grey

Cord

Linen

Mist



# Renovation Wall tiles

## FOR A SUCCESSFUL PROJECT

This paint is designed for ceramic tiles, wall tiles, border tiles, etc. Not suitable for flooring, shower trays, bathtubs, sinks and work surfaces..

Surface PREPARATION is ESSENTIAL. See Step 1 below..

Optimum product performance and adhesion is achieved after 20 days from application. Treat the surface gently, avoiding direct impact, abrasion, staining or cleaning, for the first 20 days after application.

## > STEP 1 - PREPARATION

### • CERAMIC TILES, WALL TILES, BORDER TILES, GLASS BRICKS::

wash, rinse with water then allow to dry..

### • TILE GROUTING:

Carefully clean the tile grouting with an abrasive sponge or brush to remove any residual cleaning products or any traces of mould.

**WASHING the surface with a soda-based (alkaline) cleaner is essential.**

Greasy or plastic-coated materials can affect the adhesion of the paint.

*Remove any silicone sealant before painting. Reseal after application of the paint.*

## > STEP 2 - APPLICATION

**TOOLS :** Paint mixer or wide stick • Paint roller & brush (for angles, corners, joints & finishes);

**A sachet is placed under the lid of the tin. It contains an additive that MUST be added to the paint before applying it..**

- > Empty the entire sachet into the tin of paint
- > Stir the paint with a mixer or wide stick, working around the bottom of the tin to mix it well
- > Apply.

*Once the sachet has been added, the mixture must be used within 10 days. After this time, adhesion and performance are diminished.*

This additive is compatible only with the V33 Tiling Renovation paint.

1. Start by painting the angles, corners and joints of your painting surface.
2. Distribute the paint evenly on your roller and apply from top to bottom. Follow with successive cross strokes (moving from left to right).
3. Finish from top to bottom for perfect results.

To obtain the optimal performance and resistance, two coats of paint are essential. (Touch dry: 4 hours - Recoat: 24 hours - Fully Dry: 72 hours). For bright colors, dark or porous supports, it may be necessary to apply an additional coat.

*Work on small surfaces (about 1m<sup>2</sup>) • Observe the recommended coverage rate • Do not apply the product either too thickly or too thinly • Apply the paint between 12 and 25 °C and avoid draughts • Do not stop applying the product in the centre of a surface • Do not start reapplying the product while it's still drying • Remove as much paint as possible from brushes and rollers before washing. Clean your tools with water • To clean painted surfaces, use a gentle detergent. Do not use abrasive sponges.*